

LW301-DC180



LW301-DC180

DC Fast Charger Dual Port
180kW max

KEY FEATURES

- » Upgradable power: 120, 150 or 180kW
- » Simultaneous charging
- » ISO 15118
- » CTEP Certified
- » Buy America compliant options available

LW301-DC180

Electrical

- Input Voltage: 480V AC at 50/60Hz
- Input Current: 250A
- Output Voltage: 200-1000V DC
- Output Current: 300A
- Output Power: 180kW
- Power Factor: >0.98
- Efficiency: >94% at full load
- Hardwired connection
- Dynamic power sharing in 30kW increments

Connector and Cable

- Dual CCS-1
- NACS option coming soon
- High-quality flexible cable
- Cable length 16.4'
- Trapezoidal swing arm for cable management

Networking and Communications

- Wi-Fi, Ethernet, 4G
- ISO 15118
- DIN 70121
- Over-the-air firmware updates are automatic when connected to the Lynkwell network

Environment

- Indoor and outdoor rated NEMA 3R
- Operating Temperature:
-22°F to 131°F (-30°C to 55°C)
- Storage Temperature:
-40°F to 158°F (-40°C to 70°C)
- Humidity: 95% non-condensing
- Altitude: Operational up to 6,561'
- Impact Resistance: IK10

Display and Indicators

- 10.4" touch screen
- LEDs provide highly visible EVSE status indicators

Device Mounting

- Ground
- Device dimensions (WxHxD):
31.5" X 29.5" X 80.7"
- Weight: ~992lb (450kg)

Standards and Compliance

- UL Certified
- FCC Part 15A
- OCPP 1.6J
- Energy Star

Other Features and Options

- RFID enabled
- Credit card reader available
- Buy America compliant options available

