



## EVMax+ LW101-AC80- ML

80A Level 2 Charger  
Modular EVSE

### EZ-SWAP FACEPLATE™



## KEY FEATURES

- EZ-Swap Faceplate™
- Buy American Build America (BABA) Act compliant options available
- Local load management
- Customizable backlit logo



Ask us about the option for  
**LIFETIME WARRANTY**



## LW101-AC80-ML SPECIFICATIONS

### Electrical

- Configurable current limit settings ranging from 12A to 80A
- Rated voltage: 208-240V AC at 60Hz
- Charging power: 19.2kW at 240V
- Ground fault detection 20mA CCID, auto reset
- Power measurement accuracy +/- 1.0%
- Open ground detection

### Connector and Cable

- Single SAE J1772
- High-quality flexible cable
- 18ft / 25ft cable options

### Networking and Communications

- Gateway (Wi-Fi and LTE) & non-gateway (Wi-Fi only) units savailable
- Cellular LTE CAT.M1
- Wi-Fi 2.4GHz 802.11 b/g/n
- Connect up to nine EVMax+™ non-gateway units to one EVMax+™ gateway unit
- Over-the-air firmware updates
- Network Protocol OCPP 1.6J

### Environment

- NEMA 3R rated for indoor and outdoor use
- Meets UL 50E standard for enclosures
- Operating temperature: -22°F to 122°F (-30°C to 50°C)
- Storage temperature: -22°F to 140°F (-30°C to 60°C)
- Humidity: 95% RH non-condensing
- Altitude: 15,000ft (per MIL-STD-810H, 500.6)
- Shock (per MIL-STD-810H, 516.8)
- Vibration (per MIL-STD-810H 514.8)

### Standards and Compliance

- Energy Star
- OCPP 1.6J
- FCC Part 15
- UL 2231-1, UL 2231-2, UL 2594, UL 991, UL 1998

### User Interface

- Display screen provides information about:
  - Connectivity, charging status, price per kWh, idle fee, charging time, max current output, energy dispensed, running cost, firmware version, and fault status
- Display dimensions: 2.7in (W) x 1.5in (H)
- Display resolution: 128 px x 64 px
- Customizable logo and LED color
- LED status indicators

### Status Indicators

- The LED status lights are highly visible indicators:
  - Green - available / preparing
  - Blue - charging
  - Yellow - booting / configuration / upgrading
  - Red - faulted / unavailable

### Device Specs

- Wall or pedestal mounted
- Power line knockout options available
- Bracket dimensions:  
3.4in (W) X 8.8in (H) X 0.7in (D)
- Device dimensions:  
6.1in (W) X 14.1in (H) X 4.5in (D)
- Weight: 17lb (18ft cable),  
21lb (25ft cable)



Lynkwell reserves the right to alter product offerings and specifications at any time without notice. Lynkwell disclaims any and all liability for errors, inaccuracies or incompleteness that may appear in this document. This document does not expand or otherwise modify Lynkwell's terms and conditions or product warranty expressed therein.

**MaxLite®**  
A NEW WAVE OF LIGHT

**Made in the USA  
with global parts**



Hardware manufacturing, operations, software, support,  
and service team are proudly based in the U.S.

[evmax.maxlite.com](http://evmax.maxlite.com)

MaxLite Sales: (800) 555-5629  
Lynkwell Customer Service: (833) 611-5965

Scan QR Code



Contact Form